

Cova PedMaster

Full height turnstiles



Physical
Security
Systems

Product Code - CSG 11770/11770B/11770D/11770P/11771



Find out more
Scan for more information

Description

Cova PedMaster is a Full Height Turnstiles provide secure pedestrian access control for up to 20 people per minute, with single or double configurations, access control integration, and durable construction for high-traffic restricted sites



Force Tested to 1200 Newtons

3 arm, 4 arm, double, bike and
PedGate options available

Bi-directional or single
direction

Wide range of RAL
colours available

Isometric view of post and fixing details for the COVA PedMaster
This product has additional features not demonstrated for security reasons



Construction	Available with straight arm or 3-wing 120° rotation for faster throughput Bi-directional control, fail-safe, or fail-secure Factory settings require no adjustment Handles high traffic volumes Suitable for severe operating conditions For interior and exterior installations 100% duty cycle, continuous usage capable	Finish	Polyester powder coated
Dimensions	Single Unit: 2296mm H x 1540mm WW x 1370mm D Double Unit: 2296mm H x 2400mm W x 1370mm D	Warranty	Minimum of 15 years against manufacturing defects
Flow Rate	F15 to 20 (depending on reader)		
Electrical Supply	Mains Supply: 230V 50Hz single phase rated @ 10 Amp		

Disclaimer

Fencing should be installed in accordance with BS 1722-14. Every care has been taken to ensure that all information provided in this document is accurate. CLD Fencing Systems Ltd reserves the right to change product specification at any time. Please ensure that you have the latest information which can be found on our website or by contacting our team.

Site-specific structural calculations can be provided upon request. Please contact us for further details.

Construction	Available with straight arm or 3-wing 120° rotation for faster throughput	Finish	Polyester powder coated
	Bi-directional control, fail-safe, or fail-secure		
	Factory settings require no adjustment		
	Handles high traffic volumes	Warranty	Minimum of 15 years against manufacturing defects
	Suitable for severe operating conditions		
	For interior and exterior installations		
Dimensions	100% duty cycle, continuous usage capable		
Dimensions	Single Unit: 90.4in H x 60.6in W x 53.9in D		
	Double Unit: 90.4in H x 94.5in W x 53.9in D		
Flow Rate	F15 to 20 (depending on reader)		
Electrical Supply	Mains Supply: 230V 50Hz single phase rated @ 10 Amp		

Disclaimer

Fencing should be installed in accordance with BS 1722-14. Every care has been taken to ensure that all information provided in this document is accurate. CLD Fencing Systems Ltd reserves the right to change product specification at any time. Please ensure that you have the latest information which can be found on our website or by contacting our team.

Site-specific structural calculations can be provided upon request. Please contact us for further details.