



Eastgate House
87 Eastgate
Deeping St. James
Peterborough
PE6 8HH
Tel: +44 (0) 1778 342202
Fax: +44 (0) 1778 346633

sewaco

LIMITED

Email: info@sewaco.co.uk
Web: www.sewaco.co.uk

Water Meter Boundary Boxes.

A range of underground boundary boxes are manufactured which are fully WRAS approved and certificated for use on potable water supply. All include the efficient MBS Manifold that incorporates stop tap and non return valve with top entry meter mounting point that accepts all types of screw-in water meter.

SENATE Box is suitable for all domestic and small commercial installations, available as a wet enclosure with 200 mm dia guard tube. Fitted with JG Speedfit 'push fit' socket type horizontal inlet and outlet connections.

All boundary box units are fitted with the JG range of Speedfit 'push fit' connections.

A full range of JG Speedfit 'push fit' pipe fittings are available to complement most installation requirements.

Cast iron and plastic surface boxes can be supplied for SENATE boxes.

A range of bottom entry water meters can be supplied to suit site requirements.

MBS Manifold.

The MBS manifold is an all plastic unit, with the main components manufactured from Hostaform. The manifold incorporates John Guest 'Speedfit' 25 mm pushfit couplings; Watts Ocean backflow prevention valve and 'screw-down' type stop tap valve.

The manifold has been subjected to test pressures in excess of 25 bar, with no sign of distortion or leakage.

The manifold is fully compliant with WRAS and WRC requirements for products suitable for incorporating in products for potable water supply.

MBS manifolds are incorporated in SENATE Boundary Box assemblies. The manifold can also be used as a 'stand alone' unit and in multi manifold installations.

A special TEE handle is supplied for operation of the 'screw-down' stop valve. This handle is designed to protect the valve spindle by incorporating a degree of twist to ensure that, in the event of abuse, the tee handle will fail before the valve spindle.

MBS Manifolds accept all standard bottom entry Meters fitted with 1.5" threading male connection.

Manifolds are supplied fully pressure tested to 10 bar in each Meterbox base assembly. This ensures integrity of all internal seals.

Loose manifolds are available as tested assemblies suitable for a range of applications as single or multiple assemblies.